



iPark

Parking Sensor



iPark

Parking Sensor

Product Description

TST iPark Sensor is especially designed for the detection of vehicles parked in a particular parking space. When the space is occupied the **TST iPark** sensor relays the information through LoRaWan.

LoRaWan Module

The parking sensor is surface mounted onto the road surface, and is easily removed if necessary. With a highly accurate magnetic sensor and vehicle detection algorithms it accurately detects parked vehicles. The **TST iPark** sensor is the optimal monitoring device for on-street and off-street municipal parking.



Technical Specifications

PARAMETER	VALUE
SENSOR	
Detection	3-Axis Magnetic Detection
Output	Occupied / Vacant
MECHANICAL AND ENVIRONMENT	
Operating Temperature	-40°C – +80°C
Operating Humidity	10% – 95%
Load Resistance	Up to 10 Tons
Protection Level	IP68
iPark Sensor Size	H196mm x W196mm x D28mm
POWER SPECIFICATION	
Battery Type	Lithium Battery LiSOC12
Battery Capacity	3.6V/16000mAh
Sleep Current	≤30uA
Tx Current	≤130mA
Battery Life	5 - 10 Years
RADIO SPECIFICATION	
Frequency Bands	AU915
Protocol	LoRaWan CLASS A
Max. Transmit Power	19dBm
Rx Sensitivity	BW = 125kHz, SF=7 Rx Sensitivity: - 125dBm SF = 10, Rx Sensitivity: - 133dBm SF = 12, Rx Sensitivity: - 140dBm





TST

320 Darebin Road
Fairfield VIC 3078

www.trafficltd.com.au

NSW

P: +61 2 9736 3677
F: +61 2 9736 3391
e: info@trafficltd.com.au

NT

P: +61 8 8947 0733
F: +61 8 8947 0713
e: info@trafficltd.com.au

QLD

P: +61 7 3266 1900
F: +61 7 3266 2244
e: info@trafficltd.com.au

VIC

P: +61 3 9430 0222
F: +61 3 9430 0244
e: info@trafficltd.com.au

ACT

P: +61 2 6299 7922
F: +61 2 6299 7977
e: info@trafficltd.com.au

TAS

P: +61 3 6273 1177
F: +61 3 6273 1759
e: info@trafficltd.com.au

SA

P: +61 8 8362 2385
e: info@trafficltd.com.au

WA

P: +61 8 9248 1002
F: +61 8 9209 2288
e: info@trafficltd.com.au

UNITED KINGDOM

P: +44 (0) 1159 223 797
F: +44 (0) 1159 223 836
e: info@aldridgetraffic.co.uk

