

ALDRIDGE

GO  GREEN



NEW
PRODUCT

ENVIROLITE - LANTERN HOUSING
Sustainable and 32% Lighter than aluminium



GO GREEN ENVIROLITE LANTERN HOUSING – 100% RECYCLABLE

SUSTAINABLE, ECO-FRIENDLY, 32% LIGHTER THAN ALUMINIUM, PLUS COST BENEFITS

GO GREEN Envirolite Lantern Housing robust design is equivalent to typical aluminium and polycarbonate lantern housings, withstanding the harsh Australian weather and traffic conditions within cities and suburbs.

- ✓ ECONOMIC COST BENEFITS
- ✓ 100% AUSTRALIAN MADE
- ✓ 100% RECYCLABLE
- ✓ 32% LIGHTER THAN ALUMINIUM
- ✓ DURABLE AND LONG LASTING
- ✓ SUSTAINABLY SOURCED
- ✓ PASSES ALL TRAFFIC SIGNAL REQUIREMENTS
- ✓ FLAME RETARDANT
- ✓ UV STABILISED

TTL (Traffic Technologies Ltd) has developed the **GO GREEN Envirolite Lantern Housing** incorporating eco-design principles and considering stringent traffic signalling requirements. This eco-friendly housing not only meets the necessary Australian Standards (AS-NZS-5377 and AS-2144) but contributes towards global sustainability by reducing CO2 emissions from product manufacture and energy reduction.

The **Envirolite Lantern Housing** is both *recyclable* and *lightweight* providing a durable solution without compromise. By choosing Go Green, customers are making an Envirolitenmental and responsible choice. **GO GREEN makes ECO-sense.**

TTL METHODOLOGY

TTL follows a sustainable methodology to minimise landfill waste from toxic products and reduce Envirolitenmental pollution. When the broken or obsolete lantern assemblies are sent for dismantling, TTL recovers the commodity materials; nylon, resin, metals and all other recyclable compounds from these assemblies. The materials are subsequently recycled and repurposed for the manufacture of the **Envirolite Lantern Housings** and other TTL manufactured traffic products.



| MATERIAL DESCRIPTION | FEATURES |
|--|--|
| <ul style="list-style-type: none"> Black - Flame Retarded Non-Halogenated, Non-Phosphorous Fire Retardant High Flow Heat Stabilised UV Stabilised | <ul style="list-style-type: none"> Economic cost benefits 100% recyclable as per Australian Standards: AS-NZS-5377 and AS-2144 Extremely light construction - 32% lighter than aluminium Light field insert diameter 200 or 300 mm Developed under eco-design principles Sustainable reduction of CO2 emissions Optimized strength and stability Vertical and horizontal installation High resistance to vandalism |



| TECHNICAL SPECIFICATION | |
|---------------------------|--|
| Ingress protection : | Water – (IP35) and dust-proof – (IP55) |
| Housing colours : | RAL 9005 black |
| Insert Diameter : | 200mm and 300mm |
| Mounting : | as per AS-2144 |
| Approval Certificate No : | ITS-TAN000134 |
| Approval Standards : | AS-2144, TSI-SP-045 |

| ENVIROLITE TESTING | CERTIFICATE |
|-----------------------|-----------------------|
| Change of Temperature | EN 600068-2-14 ✓ Pass |
| Cyclic Damp Heat | EN 600068-2-30 ✓ Pass |
| Random Vibration | EN 600068-2-64 ✓ Pass |
| IP5X | IEC 60529 ✓ Pass |
| Salt Mist | EN 60068-2-52 ✓ Pass |



Aldridge Traffic Systems

Unit 38, 38-46 South St.
Rydamere NSW 2116
Australia

www.trafficltd.com.au



NSW

P: +61 2 9701 9900
e: info@trafficltd.com.au

VIC

P: +61 3 9430 0222
e: info@trafficltd.com.au

SA

P: +61 3 9430 0266
e: info@trafficltd.com.au

NT

P: +61 8 8947 0733
e: info@trafficltd.com.au

ACT

P: +61 2 6299 7922
e: info@trafficltd.com.au

WA

P: +61 8 9248 1002
e: info@trafficltd.com.au

QLD

P: +61 7 3184 2000
e: info@trafficltd.com.au

TAS

P: +61 3 6273 1177
e: info@trafficltd.com.au

UNITED KINGDOM

P: +44 (0) 1159 223 797
e: info@aldridgetraffic.co.uk

